Putzmeister

Your benefits

- 4 cylinder engine for maximum power
- Hydraulic feeder to work more efficiently
- Scaper to fill easily
- Operating panel clear and user-friendly
- Chassis with automatic brake adjustment
- Optimised maintenance and service features
- Robust design ensures value retention and high resale values
- Made in Germany

Mixokret M 760 – Maximum engine power for challenging tasks

The perfect interaction of engine, compressor and hydraulic mixer drive gives the Mixokret M 760 its high performance. Large construction sites with up 50 stories or 200 m horizonal – no problem for the Mixokret M 760.

The compressor ensures that the pump operates more consistently and wear resistant. In other words, it maintains a constant material flow and reduces movements of the delivery hoses.

The oil-cooled 4-cylinder Deutz diesel engine is one of the most reliable of its kind. In idling speed, the engine regulates its speed automatically down. This makes it more quiet, saves fuel and has lower wear.

For further information related to technical details or application, please contact your local Putzmeister dealer.

Semi-dry floor screed

- **Cement screed**
- **Calcium sulphate screed** (anhydrite)
- **Magnesia screed**

Oil-cooled 4-cylinder Deutz diesel engine with an efficient compressor for maximum pump output, and enough reserve power for more challenging jobs

Air valve fitting, instruments and important indicators are all within view and easy to reach

The innovative exhaust air routing and an additional exhaust duct improve the working area.

Technical data

	M 760 DH	M 760 DHB	M 760 DHBS
Mixer drum	260 l, 200 l useful cap.	260 l, 200 l useful cap.	260 l, 200 l useful cap.
Delivery rate*	4 m³/h	4.8 m³/h	5 m³/h
Delivery pressure	8 bar	8 bar	8 bar
Delivery range**	200 m horizontally / 150 m vertically (50 storeys)		
Compressor	5.0 m³/min; cut-off pressure 8 bar		
Engine	4-cylinder Deutz diesel; 46 kW at 2,600 rpm (not available in the EU)		
Weight (fully fuelled)	1,720 kg	1,826 kg	1,900 kg
Tank capacity	60 l	60 l	60 l
Length	4,780 mm	5,075 mm	5,075 mm
Width	1,480 mm	1,480 mm	1,480 mm
Height	1,520 mm	2,431 mm	2,431 mm
Filling height	820 mm	400 mm	400 mm
Maximum grain size	16 mm	16 mm	16 mm
Chassis	braked, with automatic brake adjustment approved for speeds up to 80 km/h		
Special feature	Basis version	with hydraulic feeder	with hydraulic feeder and scraper

* The delivery rate is theoretical and depends on the pump pressure.
** The data is based on experience and depends on the material properties.

Equipment

Automatic brake adjustment	■
Car coupling	■
Central lubrication system	■
Discharge stand	■
Grease pump for lubrication system	■
Instruction manual and spare parts list	■
Lever Press with hose	■
Lifting eye	■
Reservoir gauge in control panel	■
Working lights	■
Auto-Power-Off	□
Conversion to 100 km/h	□
High-pressure cleaner	□
Light holder 24 V	□
Location system	□
Mixing time adjustment	□
Performance management	□
Special canopy paint in RAL colours/Customer labelling	□
Support feet	□
Truck coupling	□
Wear plates at the dome	□
Wear plates front end (impact protection bars)	□
Wear plates, highly wear-resistant (lateral)	□
Wear plates, plastic	□

□ Optional ■ Standard

Technical changes and errors excepted © by Putzmeister Mörtelmaschinen GmbH 2017 All rights reserved Printed in Germany (1707Sc) MT 4775 EN

Putzmeister Mörtelmaschinen GmbH
Max-Eyth-Straße 10 · 72631 Aichtal / Germany
P.O.Box 2152 · 72629 Aichtal / Germany
Tel. +49 7127 599-0 · Fax +49 7127 599-743
mm@pmw.de · www.pmmortar.de

Putzmeister