



Putzmeister

Your benefits

- Conical mixing pipe for optimum material flow
- Large hopper with bag opener
- Water pump built in for constant water flow
- Compressor with pressure cut-off to work more safe
- Worm parts easy to change according to each application

MP 25 Mixit – Maximum efficiency for processing premixed dry mortar



- **Self levelling compound**
- **Calcium sulphate screed**



- **Exterior plaster**
(lime, lime cement and insulating plaster)
- **Interior plaster**
(gypsum/gypsum-lime plaster)



Putzmeister mixer pumps are some of the most versatile machines of this type on the market. And this is also true for the MP 25 Mixit.

It handles all pumpable ready-mixed mortars such as ground coat plasters, adhesive mortars, reinforcement mortars, refractory mortars and texturing plasters etc. – both inside and outside.

Being a typical Putzmeister mixer pump, you can also completely disassemble the MP 25 Mixit with effortless ease. The modular groups can then be easily loaded into a car or carried up to the upper storey on the construction site. There the hoses are connected up and work can begin!

Your competent Putzmeister dealer will be happy to advise you on technical details and application issues.

Self levelling floor screed

Plaster/Fine plaster



Can be dismantled into manageable sections without using tools and then transported easily

Technical data

	MP 25 Mixit 3 × 400 V 50 HZ	MP 25 Mixit – Export version
Mixer drum	115 l	115 l
Delivery rate (theor.)*	25 l/min	40 l/min
Delivery pressure	40 bar	20 bar
Delivery range**	40 m horizontal, 15 m vertical	30 m horizontal, 15 m vertical
Air compressor	0,55 kW / 200 l/min	0,55 kW / 200 l/min
Pump	Worm pump D6 Power	Worm pump D 5 kurz
Engine	400 V / 50 Hz 5.5 kW at 392 rpm	400 V / 50 Hz 5.5 kW at 392 rpm
Drum drive	1.1 kW at 23 rpm	1.1 kW at 23 rpm
Water pump	0.78 kW at 3.4 m ³ /m	0.78 kW at 3.4 m ³ /m
Weight	240 kg	240 kg
Length × width × height	1324 × 728 × 1443 mm	1324 × 728 × 1443 mm
Filling height	984 mm	984 mm
Pressure connection	M35 / V 25–40	M35 / V 25–40
Maximum particle size	4 mm	4 mm
Special feature	Hose ID 25 for high-quality materials	Hose ID 35 for low-quality materials

* The delivery rate is theoretical and depends on the pump pressure.

** The data is based on experience and depends on the material properties.

Equipment

	MP 25 Mixit 3 × 400 V 50 HZ	MP 25 Mixit Export version
Air hose ½" Geka	■	■
Cleaning tool	■	■
Compressor	■	■
Hose adapter	■	■
Instruction manual with spare parts list	■	■
Mortar hose	■	■
Spray gun	■	■
Standard colour paintwork	■	■
Water pump, self-priming	■	■
NW 25 accessories	■	□
NW 35 accessories	□	■
Suction hose with filter	□	■
Air injection hood	□	□
Cable remote control + extension	□	□
Insulating plaster attachment	□	□
Spacer plates	□	□

□ Optional ■ Standard

Putzmeister Mörtelmaschinen GmbH

Max-Eyth-Straße 10 · 72631 Aichtal / Germany
 P.O.Box 2152 · 72629 Aichtal / Germany
 Tel. +49 7127 599-0 · Fax +49 7127 599-743
 mm@pmw.de · www.pmmortar.de



Putzmeister